BETTER. SMARTER. FASTER.



JCM Global's TBV™ is the better, smarter, faster solution for single note and bulk note transactions. At processing speeds of 1.7 seconds for fixed width notes, TBV is the fastest in its class, and its proven advanced technology provides the highest level of counterfeit detection. It is perfect for self-pay kiosk operations, retail safes, ticketing/transit operations, automated deposit systems and banking operations.


FEATURES

- · Single note and bulk note applications
- · Bulk note feeder accepts up to 50 notes
- · Double-locking cash box
- · Wide bezel opening
- Impact resistant and easily accessible 2,000 note cash box
- · Bulk Note Feeder (BNF) processes notes from the bottom of the stack
- Simultaneously accepts multiple denominations and currencies
- · Dirt and liquid resistant sealed bill path
- · Intelligent Cash Box (ICB®)
- · Self-centering mechanism

BENEFITS

- · One device for multiple uses
- · Quick processing of large stacks of notes
- · Adds extra layer of security
- · Easy entry of notes from 60mm to 85mm
- Increases cash handling security & reduces cash handling time
- Allows additional notes to be added on top of deposits in process
- · No need to sort banknotes prior to insertion
- · Keeps dirt and moisture out, maintaining a high acceptance rate and lowering maintenance
- · Reduces accounting variances & tracks asset number
- · Allows acceptance of most of the world currencies





BANKNOTES ACCEPTED

Width: 60 – 85mmLength: 110 – 170mm

NOTE-TO-NOTE PROCESSING SPEED

Approx. 1.7 sec, fixed widthApprox. 2.0 sec, variable width

NO. OF BANKNOTE TYPES SUPPORTED

· 100 banknote types in 4 ways

ACCEPTANCE RATE

· 98% or higher

CASH BOX CAPACITY

• 2,000 for new notes

POWER SUPPLY

· 24VDC +/- 5%

POWER CONSUMPTION

· Idling: 0.2A

· In Operation: 2.0A

· Peak: 5.3A (max 3.3A for 3 sec)

INTERFACE

· Photo-coupler (ID003), RS232 (ID003), USB 2.0, ccTalk

SOFTWARE DOWNLOAD

- · Through USB port
- · Download tool available

OPERATION TEMPERATURE

- · -15 to 60 °C (5 to 140 °F) without BNF
- · 5 to 50 °C (41 to 122 °F) with BNF

INSTALLATION

· Indoors and Outdoors

DIMENSIONS (HxWxD)

- With BNF 475.8x114x468.9mm (18.73x4.49x18.46")
- With Shutter Bezel 483.5x140x289.17mm (19.04x5.51x11.38")

OPTIONS

- \cdot Standard plastic single note bezel
- \cdot Metal single note shutter bezel
- · LD frame (stackerless frame w/o cash box)
- · Intelligent Cash Box (ICB®)



No cash box option (stackerless)







SINGLE NOTE SHUTTER BEZEL



EMEA: 49.211.5306.4550 · JAPAN: 81.6.6703.8400 · US: 702.651.0000 · US: 800.683.7248

jcmglobal.com