

# SK1-211/SK1-311 HIGH-SPEED KIOSK PRINTER

### Features

- 250mm/sec high speed printing
- Easy paper loading with side open head
- Long service life (150Km abrasion resistance and 2 million cuts)
- Robust cutter selectable for full cut or partial cut
- Lineup of presenter with LED bezel
- Available for Utility driver with Remote Status monitor







SK1-211



## SK1-211/SK1-311

### **Features**

250mm/sec high speed printing

Easy paper loading with side open head

Robust cutter selectable for full cut or partial cut

Lineup of presenter with LED bezel

Fine graphic printing

Utility driver with Remote Status monitor

### **Applications**

Gas pump

**Parking** 

Self service kiosk

Gaming and Lottery

Queue systems

Vending machine





Specifications	SK1-211	SK1-311
Printing method	Direct line thermal	
Resolution	203dpi (8 dots/mm)	
Number of dots	Max.448 dots	Max.640 dots
Printing width	56/54mm	80/72/56/54mm
Paper width	60/58mm	83/80/60/58mm
Printing speed	Max.250mm/sec.	
Paper style	Receipt paper / Label paper	
Paper thickness	0.059 to 0.15mm (52g/m <sup>2</sup> to 128g/m <sup>2</sup> )	
Paper roll diameter	Max. φ 120mm(φ 200mm available)	
Character font	8x16, 12x24 dots	
Barcode	JAN8/13, CODE39, ITF, CODABAR, CODE128, UPC-A/E	
	(Option) QR, Maxicode, PDF417	
Paper sensor	Paper end, Paper near end, Black mark & Label gap (Option)	
Paper loading	Head open or Auto loading	
Auto cutter	Full cut or partial cut (Command selectable)	
Interface	RS232C Serial + USB2.0	
Emulations	ESC/POS™ Conformity	
Power supply	24VDC±5%	
Operating temperature	-20 to 60 °C, 20% to 85%RH (Non-condensation)	
Storage temperature	-30 to 70 ℃	
Reliability	Print head : 150km, 200million pulses	
	Auto Cutter: 2,000,000 cuts (Specified paper)	
Safety standards	CE, FCC, VCCI	
Overall dimensions	104(W)×145.5(D)×85.4(H)mm	127(W)×145.5(D)×85.4(H)mm
Mass	Approx. 525g	Approx. 630g

\*ESC/POS is a registered trademark of Seiko Epson Corporation.

\*All specifications are subject to change without notice.

Distributed by







www.sanei-elec.co.jp